

Specifications

	Model	
	Bosch 32	Bosch 32Q
Part Number	KM3211WH	KM3211WHQ
L/min (25 °C Rise)	32	32
Gas Input-Low	25 MJ/H	25 MJ/H
Gas Input-High	250 MJ/H	250 MJ/H
Star Rating	4.8	4.8
Antifrost	Standard	Standard
Type	Internal* or External	Internal* or External
Installation	Wall Hung	Wall Hung
Air Supply / Exhaust	Power Flued	Power Flued
Gas Type	NG / LP	NG / LP
Min. pressure for max flow	200 kPa	200 kPa
Max. allowable inlet water pressure	900 kPa	900 kPa
Min. flow rate (L/min)	3.5	3.5
Unit Height (mm)	615	615
Unit Width (mm)	464	464
Unit Depth (mm)	240	240
Unit Weight (KG)	29	32
Power Supply	240 VAC	240 VAC
Power Consumption	NG - 100W / LP - 115W	NG - 135W / LP - 150W
Warranty	In domestic applications – 3 year parts and labour, 10 years heat exchanger (part only) In commercial applications – 2 year parts and labour, 5 year heat exchanger (part only)	
Pipe Connection Size		
Water Inlet	20 mm (3/4")	20 mm (3/4")
Hot Water Outlet	20 mm (3/4")	20 mm (3/4")
Hot Water Return	–	15 mm (1/2")
Gas Inlet	20 mm (3/4")	20 mm (3/4")